

'for all conditions'



**Entel UK**

# HT800 - At the frontiers of safety



Heavy duty locking accessory connector

CSA640E optional rapid charger

**Intrinsically Safe** - Radios for use in the explosive environments of oil and gas installations, such as tankers or drilling platforms, or in gas-laden atmospheres encountered by the emergency services must be designed and constructed to be totally safe. Note: For land applications in EU/EFTA countries it is now a legal requirement to be compliant with the European ATEX Directive. Please see our HT900 Series product brochure.

**Submersible** - The unique and advanced HT800 Series conforms to all aspects of UL Certification for portables used in hazardous environments. It further exceeds the requirements by being completely submersible - all other radios in this class are merely splashproof. Entel believe that non submersible radios have no place in the harsh world of maritime and terrestrial high-risk environments.

**Ergonomic** - Large rubber armoured volume control and side grips make HT800 series easy to grip with wet or gloved hands, and has indispensable high visibility displays.

**Built for hostile environments** - HT800 radios are unique in offering such a full specification. They are built without compromise to deliver superb, consistent performance in the most hostile environments encountered on land or at sea.

**Powerful** - Delivers a maximum of five watts RF power on VHF and four watts on UHF, both switchable to one watt low power should you wish to conserve battery life.

**Feature Rich - Simple To Use!** - With all its technological advances the HT800 series remains very simple to use, with the majority of its features accessed by a single key depression.

**Superior Audio Quality** - Latest compander noise reduction technology delivers loud and crisp audio no matter what environment you are in.

**Battery Life Indicator** - Continually monitors battery state for your safety and convenience.

**Built In Voice Scrambler** (HT840 only) - Enabled at the press of a button, this feature ensures privacy between you and other HT840 radios used in your system. Your radio calls will be loud, crisp and clear whilst potential eavesdroppers monitoring the same channel will hear unintelligible garble.

**Lithium-Ion Battery Technology** - This very latest battery technology gives you three big advantages:

1. Huge fifteen hour duty cycle with supplied CNB840E battery pack.
2. Not prone to the dreaded memory effect that Nicad and Ni-MH battery packs suffer from, therefore no more need to fully discharge your battery pack before charging!
3. Stores a charge up to three times longer than a Nicad.

**A/B Quick Access Channels** (HT840 only) - Immediately recalls two user assigned channels, for speed and convenience.

**VOX** - Hands free operation when used with a VOX accessory.

**Scanning** - Ultra fast MEM® scan searches through memorised channels to ensure no lost calls.

**Private Channels** (HT840 only) - The HT840 has a capacity for an additional 36 private channels, which can be programmed by your dealer.

**Three Year Warranty** - The HT800 series transceiver is supported by a three year manufacturers warranty.



\*\* If your application is inside EU/EFTA countries, or for a seagoing vessel/mobile offshore unit under 500 gross tonnes, please refer to our HT900 Series ATEX intrinsically safe range.

# HT800 series

The HT800 Series is UL Certified, and approved for use in hazardous locations. The certification code is interpreted as follows:

Class I Group A  
 Group B  
 Group C  
 Group D } Flammable gases & vapours

### Division I

Locations where hazardous materials are continuously, frequently or intermittently present under normal operating conditions

### T3

Indicates maximum surface temperature should not exceed 200°C

Class I, Div I,  
 Groups A,B,C,D T3



HT840



HT820/880

In order to address the different applications, the following variants of HT800 Series are available:

Model	Land	Marine	VHF	UHF	Channels	Submersible
HT820	✓	✗	✓	✗	128 - PC programmable	✓
HT840	✗	✓	✓	✗	Pre programmed 55 channels	✓
HT880	✓	✓	✗	✓	128 - PC programmable	✓



# HT800 UL certified & approved accessories



**CNB840E**



**\*CSA640E**



**\*CSB640E**



**CMP840**



**EA19/840**



**EA15/840**



**EPT40/840**



**CXR5/840**



**CXR16/840**



**CHP800/HS**



**CHP800/HD**



**CLC940**

## Accessories not pictured

- \***CST640E** Six pod battery analyser
- \***CCA230** 230 volt, trickle charger
- \***CCA12** 12 volt, trickle charger
- \***CXW640** Antenna adaptor for external aerial connection

\*These accessories must only be used outside hazardous area location

- EHP840** Covert style earpiece
- CAT20IS** Spare antenna for HT920
- CAT40IS** Spare antenna for HT940
- CAT80IS** Spare antenna for HT980

For the latest range of accessories visit [www.entel.co.uk](http://www.entel.co.uk)

\*\* Use of non Entel approved accessories will invalidate your UL intrinsically safe approval.

# technical specifications



General - HT840	
RF power output	5 Watts (high) 1 Watt (low)
Frequency range	156.000 to 163.275 MHz
Channels	All currently allocated International, USA and Canadian channels, with the programmable option to limit available channels
Private channels	36 (dealer programmable)
Operating voltage	7.4v DC
Temperature range	-20°C to +50°C
Current drain:	
Standby	60mA
Receive	200mA
Transmit	1500mA (high) 750mA (low)
Duty Cycle (5/5/90)	15 hours (high) / 19 hours (low)
Dimensions	130mm(h) x 59mm(w) x 33mm(d)
Weight	296g (with battery and aerial)

General - HT820 / HT880	
RF power output	5 Watts (HT820) 4 Watt (HT980)
Frequency range (UHF)	TX 425 to 470MHz RX 438 to 470Mhz
Frequency range (VHF)	TX 148 to 170MHz RX 148 to 170MHz
Channels	128
Channel spacing	25KHz (wide) 12.5KHz (narrow)
Operating Voltage	7.4v DC
Temperature range	-20°C to +50°C
Current drain:	
Standby	50mA
Recieve	160mA
Transmit	1800mA (high) 1000mA (low)
Duty cycle (5/5/90)	14 hours (high) / 18 hours (low)
Dimensions	130mm(h) x 59mm(w) x 33mm(d)
Weight	296g (with battery and aerial)

Supplied Accessories	
CNB840E	7.4v, 1800mAh Li-Ion battery
CBH640	Spring loaded belt clip
	High efficiency antenna
	User manual

\*\*Full & detailed specification available on request

## Complete HT Series application guide for land and marine models:-

Model	Land	Marine	VHF	UHF	ATEX (I.S)	U.L (I.S)	Channels	PMR446	GMDSS
HT446	✓	✗	✗	✓	✗	✗	8	✓	✗
HT640	✗	✓	✓	✗	✗	✗	55 marine	✗	✗
HT720	✓	✗	✓	✗	✗	✗	128	✗	✗
HT780	✓	✓	✗	✓	✗	✗	128	✗	✗
HT820	✓	✗	✓	✗	✗	✓	128	✗	✗
HT840	✗	✓	✓	✗	✗	✓	128	✗	✗
HT880	✓	✓	✗	✓	✗	✓	128	✗	✗
HT920	✓	✗	✓	✗	✓	✗	128	✗	✗
HT940	✗	✓	✓	✗	✓	✗	128	✗	✗
HT980	✓	✓	✗	✓	✓	✗	128	✗	✗
HT70	✗	✓	✓	✗	✗	✗	upto 55 marine	✗	✓

I.S = intrinsically safe for hazardous area applications

## Entel UK Ltd

3rd Floor, Ridgeway House  
12 Elstree Way, Borehamwood  
Hertfordshire WD6 1JL  
United Kingdom

Tel: +44 (0)20 8236 0032

Fax: +44 (0)20 8236 0082

Email: sales@entel.co.uk

[www.entel.co.uk](http://www.entel.co.uk)

'the professional's choice'



# 'storm survivor' by Entel

## HT800 Series

UL Certified

Intrinsically Safe,

Class I, Div I, Groups A, B, C, D T3

Class I, Zone 0, IIC



**Submersible**

**Dependable**

**Tough**



**Entel UK**